

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

B3 Aqua Scan Mat - Gloss Paint

**Product no.**

934-935

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Plastic, leather and vinyl paint

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

HBC System Smarttool Production ApS

Hobrovej 961-963

9530 Støvring

Denmark

tel:+45 70 22 70 70

**Contact person**

Vibeke Jørgensen

**E-mail**

info@hbc-system.com

**SDS date**

2016-06-30

**SDS Version**

1.0

### 1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Carc. 1B; H350

Muta. 2; H341

STOT SE 3; H336

See full text of H-phrases in section 2.2.

### 2.2. Label elements

**Hazard pictogram(s)****Signal word**

Danger

### Hazard statement(s)

May cause cancer. (H350)  
 Suspected of causing genetic defects. (H341)  
 May cause drowsiness or dizziness. (H336)

<b>Safety statement(s)</b>	General	-
	Prevention	Obtain special instructions before use. (P201). Use personal protective equipment as required. (P281).
	Response	IF exposed or concerned: Get medical advice/attention. (P308+P313).
	Storage	Store in a well-ventilated place. Keep container tightly closed. (P403+P233).
	Disposal	-

### Identity of the substances primarily responsible for the major health hazards

Urethanerubber

### 2.3. Other hazards

This product contains substances which are considered or proven to be carcinogenic.

### Additional labelling

-

### Additional warnings

-

### VOC

VOC-MAX: 220 g/l, MAXIMUM VOC CONTENT (B/e): 840 g/l.

## SECTION 3: Composition/information on ingredients

### 3.1/3.2. Substances/Mixtures

NAME: Urethanerubber  
 IDENTIFICATION NOS.: CAS-no: 94766-07-1 EC-no: 200-123-1 Index-no: 607-149-00-6  
 CONTENT: 15-25%  
 CLP CLASSIFICATION: Acute Tox. 4, STOT SE 3, Muta. 2, Carc. 1B  
 H302, H336, H341, H350

NAME: (2-methoxymethylethoxy)propanol  
 IDENTIFICATION NOS.: CAS-no: 34590-94-8 EC-no: 252-104-2  
 CONTENT: 5-10%  
 CLP CLASSIFICATION: NA  
 NOTE: S

NAME: DIPHOSPHORIC,ACID,TETRAPOTASSIUM,SALT  
 IDENTIFICATION NOS.: CAS-no: 7320-34-5 EC-no: 230-785-7  
 CONTENT: <1%  
 CLP CLASSIFICATION: Skin Irrit. 2, Eye Irrit. 2  
 H315, H319

(\*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.  
 S = Organic solvent

### Other informations

ATEmix(oral) > 2000

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.  
 Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

#### Inhalation

Get the injured person into fresh air. Make sure there is always someone with the injured person. Prevent shock by keeping the injured person warm and calm. If the person stops breathing, give mouth-to-mouth resuscitation. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip.  
 Call an ambulance.

#### Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

#### **Eye contact**

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

#### **Ingestion**

In the case of ingestion, contact a doctor immediately and take this safety data sheet or the label from the material with you. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down so that no vomit runs back into the mouth and throat. Prevent shock by keeping the injured person warm and calm. Give mouth-to-mouth resuscitation if breathing stops. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip. Call an ambulance.

#### **Burns**

Not applicable

#### **4.2. Most important symptoms and effects, both acute and delayed**

Carcinogenic effects: This product contains substances which are considered or proven to be carcinogenic. The danger may lie in inhalation, skin contact or ingestion.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

IF exposed or concerned:  
Get immediate medical advice/attention.

#### **Information to medics**

Bring this safety data sheet.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

#### **5.2. Special hazards arising from the substance or mixture**

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Nitrogen oxides. Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Avoid inhalation of vapours from waste material. Avoid direct contact with spilled substances.

#### **6.2. Environmental precautions**

No specific requirements.

#### **6.3. Methods and material for containment and cleaning up**

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

#### **6.4. Reference to other sections**

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

#### **7.2. Conditions for safe storage, including any incompatibilities**

Always store in containers of the same material as the original.

### Storage temperature

No data available.

### 7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### OEL

(2-methoxymethylethoxy)propanol (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 308 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): - ppm | - mg/m<sup>3</sup>

Comments: Sk (Sk = Can be absorbed through skin. )

#### DNEL / PNEC

### 8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

#### General recommendations

Observe general occupational hygiene.

#### Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

#### Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

#### Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

#### Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible collect spillage during work.

### Individual protection measures, such as personal protective equipment



#### Generally

Use only CE marked protective equipment.

#### Respiratory Equipment

Recommended: A. Class 1 (low capacity). Brown

#### Skin protection

Special work clothing should be used. When working with this product for a long period of time, use a protective suit.

#### Hand protection

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for help on the glove type. Please note that elastic gloves stretch when used. The thickness of the gloves, and therefore their penetration time, will be reduced. Moreover, the temperature of the glove in use is about 35°C, while the standard test, EN 374-3, is done at 23°C. The penetration time is therefore reduced by a factor of 3.

#### Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm <sup>3</sup> )
Liquid	Various colours	Characteristic	-	-	-

#### Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	100	-

#### Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
70	-	-
Explosion limits (Vol %)	Oxidizing properties	
-	-	

#### Solubility

Solubility in water	n-octanol/water coefficient
Soluble	-

### 9.2. Other information

Solubility in fat	Additional information
-	N/A

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

### 10.3. Possibility of hazardous reactions

No special

### 10.4. Conditions to avoid

Do not expose to heat (e.g. sunlight), because it can lead to excess pressure.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Substance	Species	Test	Route of exposure	Result
DIPHOSPHORIC,ACID,TETRAPOTAS	Rabbit	LD50		> 4640 mg/kg
Sl...	Rabbit	LD50	Oral	5,4 ml/kg
(2-methoxymethylethoxy)propano...	Rabbit	LD50		10 ml/kg
(2-methoxymethylethoxy)propano...	Dog	LD50	Oral	7500 mg/kg
(2-methoxymethylethoxy)propano...	Rat	LD50	Oral	1809,0 mg/kg
Urethanerubber				

#### Skin corrosion/irritation

Data on substance: DIPHOSPHORIC,ACID,TETRAPOTASSIUM,SALT

#### Serious eye damage/irritation

Data on substance: DIPHOSPHORIC,ACID,TETRAPOTASSIUM,SALT  
Test: OECD Guideline 405

#### Respiratory or skin sensitisation

No data available.

#### Germ cell mutagenicity

Suspected of causing genetic defects.

#### Carcinogenicity

May cause cancer.

#### Reproductive toxicity

No data available.

#### STOT-single exposure

According to EC-Regulation 1907/2006 (REACH)

May cause drowsiness or dizziness.

**STOT-repeated exposure**

No data available.

**Aspiration hazard**

No data available.

**Long term effects**

Carcinogenic effects: This product contains substances which are considered or proven to be carcinogenic. The danger may lie in inhalation, skin contact or ingestion.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Substance	Species	Test	Test duration	Result
No data available.				

**12.2. Persistence and degradability**

Substance	Biodegradability	Test	Result
No data available.			

**12.3. Bioaccumulative potential**

Substance	Potential bioaccumulation	LogPow	BFC
(2-methoxymethylethoxy)propano...	No	-0,35	No data available

**12.4. Mobility in soil**

(2-methoxymethylethoxy)propano...: Log Koc= -0,198765, Calculated from LogPow ().

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

No special

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

The product is covered by the regulations on dangerous waste.

**Waste**

EWC code

-

**Specific labelling**

-

**Contaminated packing**

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

**SECTION 14: Transport information**

Not listed as dangerous goods under ADR and IMDG regulations.

**14.1 – 14.4**

**ADR/RID**

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

Notes

Tunnel restriction code

**IMDG**

UN-no.

Proper Shipping Name

Class

PG\*

EmS

MP\*\*

Hazardous constituent

▼ IATA/ICAO  
UN-no.  
Proper Shipping Name  
Class  
PG\*

#### 14.5. Environmental hazards

-

#### 14.6. Special precautions for user

-

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC. Only for industrial use. Pregnant and nursing women must not be exposed to the effects of this product. The risk, and possible technical precautions or design of the workplace to avoid such risk, must therefore be evaluated.

#### Demands for specific education

-

#### Additional information

#### Sources

COUNCIL DIRECTIVE 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

IDirective 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

EC Regulation 1272/2008 (CLP).

EC regulation 1907/2006 (REACH).

### 15.2. Chemical safety assessment

No

## SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H341 - Suspected of causing genetic defects.

H350 - May cause cancer.

### The full text of identified uses as mentioned in section 1

-

### Other symbols mentioned in section 2

-

### Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

According to EC-Regulation 1907/2006 (REACH)



The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

**The safety data sheet is validated by**

kbb

**Date of last essential change  
(First cipher in SDS version)**

-

**Date of last minor change  
(Last cipher in SDS version)**

-

---

ALPHAOMEGA. Licens nr.:3021486427, HBC SYSTEM Danmark  
[www.chymeia.com](http://www.chymeia.com)