

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

NP 1420 - Thinner

Product no.

NP1420

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Industrial use

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

HBC System Smarttool Production ApS

Hobrovej 961-963

9530 Støvring

Denmark

tel:+45 70 22 70 70

Contact person

Vibeke Jørgensen

E-mail

info@hbc-system.com

SDS date

2016-05-26

SDS Version

3.0

1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226

Asp. Tox. 1; H304

Skin Irrit. 2; H315

STOT SE 3; H336

STOT SE 3; H335

Aquatic Chronic 2; H411

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

- Flammable liquid and vapour. (H226)
- May be fatal if swallowed and enters airways. (H304)
- Causes skin irritation. (H315)
- May cause drowsiness or dizziness. (H336)
- May cause respiratory irritation. (H335)
- Toxic to aquatic life with long lasting effects. (H411)

| | | |
|----------------------------|------------|---|
| Safety statement(s) | General | - |
| | Prevention | Avoid release to the environment. (P273). Wear protective gloves/protective clothing/eye protection. (P280). |
| | Response | Do NOT induce vomiting. (P331). IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310). |
| | Storage | Store in a well-ventilated place. Keep cool. (P403+P235). |
| | Disposal | Dispose of contents/container to an approved waste disposal plant. (P501). |

Identity of the substances primarily responsible for the major health hazards

n-butyl acetate, Solvent naphtha (petroleum), light arom. Low boiling point naphtha - unspecified [A complex combi, Solvent naphtha (coal) Light Oil Extract Residues, high boiling [The distillate from either high

2.3. Other hazards

This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.
This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

Additional labelling

-

Additional warnings

-

VOC

VOC-MAX: 720 g/l, MAXIMUM VOC CONTENT (B/a1): 850 g/l.

SECTION 3: Composition/information on ingredients

▼ **3.1/3.2. Substances/Mixtures**

NAME: n-butyl acetate
 IDENTIFICATION NOS.: CAS-no: 123-86-4 EC-no: 204-658-1 REACH-no: 01-2119485493-29 Index-no: 607-025-00-1
 CONTENT: 15-25%
 CLP CLASSIFICATION: Flam. Liq. 3, STOT SE 3
 H226, H336, EUH066
 NOTE: S

NAME: 2-butoxyethyl acetate butylglycol acetate
 IDENTIFICATION NOS.: CAS-no: 112-07-2 EC-no: 203-933-3 Index-no: 607-038-00-2
 CONTENT: 15-25%
 CLP CLASSIFICATION: Acute Tox. 4
 H312, H332
 NOTE: S

NAME: Solvent naphtha (petroleum), light arom. Low boiling point naphtha - unspecified [A complex combi
 IDENTIFICATION NOS.: CAS-no: 64742-95-6 EC-no: 265-199-0 Index-no: 649-356-00-4
 CONTENT: 15-25%
 CLP CLASSIFICATION: Flam. Liq. 3, STOT SE 3, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2

According to EC-Regulation 1907/2006 (REACH)

H226, H304, H315, H335, H336, H411

NAME: Solvent naphtha (coal) Light Oil Extract Residues, high boiling [The distillate from either high
 IDENTIFICATION NOS.: CAS-no: 65996-79-4 EC-no: 266-013-0 Index-no: 648-020-00-4
 CONTENT: 15-25%
 CLP CLASSIFICATION: STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2
 H304, H335, H336, H411
 NOTE: S

NAME: 1,2,4-trimethylbenzene
 IDENTIFICATION NOS.: CAS-no: 95-63-6 EC-no: 202-436-9 Index-no: 601-043-00-3
 CONTENT: 5-10%
 CLP CLASSIFICATION: Flam. Liq. 3, Acute Tox. 4, STOT SE 3, Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2
 H226, H315, H319, H332, H335, H411
 NOTE: S

NAME: 2-methoxy-1-methylethyl acetate
 IDENTIFICATION NOS.: CAS-no: 108-65-6 EC-no: 203-603-9 REACH-no: 01-2119475791-29-xxxx Index-no: 607-195-00-7
 CONTENT: 5-10%
 CLP CLASSIFICATION: Flam. Liq. 3
 H226
 NOTE: S

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.
 S = Organic solvent

Other informations

ATEmix(inhale, vapour) > 20
 ATEmix(inhale, dust/mist) > 20000
 ATEmix(dermal) > 2000
 ATEmix(oral) > 2000
 Eye Cat. 2 Sum = $\sum(C_i/S(G)CL_i) = 0,64 - 0,96$
 Skin Cat. 2 Sum = $\sum(C_i/S(G)CL_i) = 1,92 - 2,88$
 N chronic (CAT 2) Sum = $\sum(C_i/M(\text{chronic})) * 25 * 0.1 * 10^{\wedge}CAT_i = 1,248 - 1,872$

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
 Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the injured person into fresh air. Make sure there is always someone with the injured person. Prevent shock by keeping the injured person warm and calm. If the person stops breathing, give mouth-to-mouth resuscitation. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip.
 Call an ambulance.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

Ingestion

In the case of ingestion, contact a doctor immediately and take this safety data sheet or the label from the material with you. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down so that no vomit runs back into the mouth and throat. Prevent shock by keeping the injured person warm and calm. Give mouth-to-mouth resuscitation if breathing stops. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip.
 Call an ambulance.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc.

Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material. Avoid direct contact with spilled substances. Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of a leakage to the surroundings, contact the local environmental authorities. Consider putting up waste collecting trays/basins to prevent leakage to the surroundings.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Consider putting up waste collecting trays/basins to prevent leakage to the surroundings. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

2-methoxy-1-methylethyl acetate (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 274 mg/m³

Short-term exposure limit (15-minute reference period): 100 ppm | 548 mg/m³

Comments: Sk (Sk = Can be absorbed through skin.)

1,2,4-trimethylbenzene (EH40, 2011)

Long-term exposure limit (8-hour TWA reference period): 20 ppm | 100 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Solvent naphtha (petroleum), light arom. Low boiling point... (AT, 2008)

Long-term exposure limit (8-hour TWA reference period): - ppm | 5 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | 10 mg/m³

2-butoxyethyl acetate butylglycol acetate (EH40/2005, 2008)

Long-term exposure limit (8-hour TWA reference period): 20 ppm | - mg/m³

Short-term exposure limit (15-minute reference period): 50 ppm | - mg/m³

Comments: Sk (Sk = Can be absorbed through skin.)

n-butyl acetate (EH40/2005, 2008)

Long-term exposure limit (8-hour TWA reference period): 150 ppm | 724 mg/m³

Short-term exposure limit (15-minute reference period): 200 ppm | 966 mg/m³

DNEL / PNEC

DNEL (n-butyl acetate): 102,34 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - General population

DNEL (n-butyl acetate): 960 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - Workers

DNEL (n-butyl acetate): 960 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - Workers

DNEL (n-butyl acetate): 480 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Systemic effects - Workers

DNEL (n-butyl acetate): 480 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - Workers

DNEL (n-butyl acetate): 859,7 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Systemic effects - General population

DNEL (n-butyl acetate): 102,34 mg/m³

Exposure: Inhalation

Duration of Exposure: Long term – Local effects - General population

DNEL (n-butyl acetate): 859,7 mg/m³

Exposure: Inhalation

Duration of Exposure: Short term – Local effects - General population

PNEC (n-butyl acetate): 35,6 mg/L

Exposure: Sewage Treatment Plant

PNEC (n-butyl acetate): 0,18 mg/L

Exposure: Freshwater

According to EC-Regulation 1907/2006 (REACH)

PNEC (n-butyl acetate): 0,018 mg/L
Exposure: Marine water

PNEC (n-butyl acetate): 0,36 mg/L
Exposure: Intermittent release

PNEC (n-butyl acetate): 0,981 mg/kg
Exposure: Freshwater sediment

PNEC (n-butyl acetate): 0,0981 mg/kg
Exposure: Marine water sediment

PNEC (n-butyl acetate): 0,09903 mg/kg
Exposure: Soil

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible collect spillage during work.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Recommended: AX. Brown

Skin protection

Special work clothing should be used. When working with this product for a long period of time, use a protective suit.

Hand protection

Recommended: Polyvinyl alcohol (PVA). : NA

Eye protection

Use safety glasses with a side shield.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Form | Colour | Odour | pH | Viscosity | Density (g/cm ³) |
|--------------------|------------|--------------------|----|-------------------------|------------------------------|
| Liquid | Colourless | Characteristic | - | - | - |
| Phase changes | | | | | |
| Melting point (°C) | | Boiling point (°C) | | Vapour pressure (mm Hg) | |
| - | | 37 | | - | |

Data on fire and explosion hazards

| | | |
|--------------------------|----------------------|--------------------|
| Flashpoint (°C) | Ignition (°C) | Self ignition (°C) |
| 38 | - | - |
| Explosion limits (Vol %) | Oxidizing properties | |
| - | - | |

Solubility

| | |
|---------------------|-----------------------------|
| Solubility in water | n-octanol/water coefficient |
| Insoluble | - |

9.2. Other information

| | |
|-------------------|------------------------|
| Solubility in fat | Additional information |
| - | N/A |

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity. Do not expose to heat (e.g. sunlight), because it can lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

| Substance | Species | Test | Route of exposure | Result |
|-----------------------------------|------------|------|-------------------|--------------|
| 2-methoxy-1-methylethyl acetat... | Rat | LD50 | Oral | 8532 mg/kg |
| 2-methoxy-1-methylethyl acetat... | Rabbit | LD50 | | > 5000 mg/kg |
| 2-methoxy-1-methylethyl acetat... | Guinea pig | LD50 | Intraperitoneal | 750 mg/kg |
| 1,2,4-trimethylbenzene | Rat | LC50 | Oral | 5000 mg/kg |
| 1,2,4-trimethylbenzene | Rat | LC50 | Inhalation | 18000 mg/m3 |
| Solvent naphtha (petroleum), ... | Rat | LD50 | Oral | 8400 mg/kg |
| Solvent naphtha (petroleum), ... | Rabbit | LD50 | Dermal | 3,48 g/kg |
| 2-butoxyethyl acetate butylg... | Rat | LD50 | Oral | 2400 mg/kg |
| 2-butoxyethyl acetate butylg... | Rabbit | LD50 | | 1500 mg/kg |
| 2-butoxyethyl acetate butylg... | Guinea pig | LD50 | Oral | 3200 mg/kg |
| n-butyl acetate | Rat | LD50 | Oral | 10768 g/kg |
| n-butyl acetate | Rabbit | LD50 | | > 5000 mg/kg |
| n-butyl acetate | Rat | LD50 | Oral | > 6400 mg/kg |
| n-butyl acetate | Rat | LC50 | Inhalation | 2000 ppm |
| n-butyl acetate | Rat | LC50 | Inhalation | 21.1 mg/l/4h |

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

No data available.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

This product contains substances that can give chemical pneumonia if inhaled. The symptoms of chemical pneumonia can appear after several hours.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

12.1. Toxicity

| Substance | Species | Test | Test duration | Result |
|-----------------------------------|------------|------|---------------|------------|
| 2-methoxy-1-methylethyl acetat... | Fish | LC50 | 96 h | 120 µg/L |
| 1,2,4-trimethylbenzene | Crustacean | LC50 | 96 H | 5100 µg/L |
| 1,2,4-trimethylbenzene | Fish | LC50 | 96 H | 5000 µg/L |
| n-butyl acetate | Daphnia | EC50 | 24 H | 205 mg/L |
| n-butyl acetate | Fish | LC50 | 96 H | 100 mg/L |
| n-butyl acetate | Crustacean | LC50 | 48 h | 32000 µg/L |

12.2. Persistence and degradability

| Substance | Biodegradability | Test | Result |
|-----------------|------------------|-------------------|-------------------|
| n-butyl acetate | Yes | No data available | No data available |

12.3. Bioaccumulative potential

| Substance | Potential bioaccumulation | LogPow | BFC |
|-----------------------------------|---------------------------|--------|-------------------|
| 2-methoxy-1-methylethyl acetat... | No | 0,56 | No data available |
| 1,2,4-trimethylbenzene | Yes | 3,63 | 120 |
| 2-butoxyethyl acetate butylg... | No | 1,51 | No data available |
| n-butyl acetate | No | 1,78 | No data available |

12.4. Mobility in soil

2-methoxy-1-methylethyl acetat...: Log Koc= 0,521864, Calculated from LogPow (High mobility potential.).
 1,2,4-trimethylbenzene : Log Koc= 2,952997, Calculated from LogPow (Moderate mobility potential.).
 2-butoxyethyl acetate butylg...: Log Koc= 1,274169, Calculated from LogPow (High mobility potential.).
 n-butyl acetate: Log Koc= 1,487982, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

This product contains ecotoxic substances which can have damaging effects on water-organisms. This product contains substances which can cause undesirable long-term effects in the water environment, due to its poor biodegradability. This product contains substances which can accumulate in the food chain because they are bioaccumulative substances. Bioaccumulative substances can accumulate in fat tissue and are not easily secreted.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code
08 01 11

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

ADR/RID

| | |
|---|--|
| 14.1. UN number | 1263 |
| 14.2. UN proper shipping name | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| 14.3. Transport hazard class(es) | 3 |
| 14.4. Packing group | III |
| Notes | - |
| Tunnel restriction code | D/E |

IMDG

| | |
|------------------------------|--|
| UN-no. | 1263 |
| Proper Shipping Name | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Class | 3 |
| PG* | III |
| EmS | F-E, S-E |
| MP** | Yes |
| Hazardous constituent | - |

▼ IATA/ICAO

| | |
|-----------------------------|--|
| UN-no. | |
| Proper Shipping Name | |
| Class | |
| PG* | |

14.5. Environmental hazards

This product contains substances which can cause undesirable long-term effects in the water environment, due to its poor biodegradability.

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC.

Demands for specific education

-

Additional information

Sources

COUNCIL DIRECTIVE 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

IDirective 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

EC Regulation 1272/2008 (CLP).

EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H312 - Harmful in contact with skin.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.
EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2

-

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

kbb

Date of last essential change (First cipher in SDS version)

2015-11-12

Date of last minor change (Last cipher in SDS version)

2015-11-12